

PART NUMBER: EL2157-2S28S1X

2-No Tabs and Shell Pins 1-3u" 2-6u"  
3-15u" 4-30u"  
5-50u" F-GOLD FLASH



REVISION RECORD 修改紀錄					
REV	ECD	DESCRIPTION	DATE	DRFT	CHKD

**MECHANICAL:**

- 1.HOUSING:LCP BLACK, UL 94V-0
- 2.CONTACT:PHOSPHOR BRONZE T=0.30MM
- 3.PLATING:6U" PLATING AT CONTACT AREA, MATTE TIN AT TAIL 100U MIN., NICKEL 30U MIN. OVER ALL.
- 4.SHELL:BRASS T=0.20
- 5.OPERATING LIFE:750 CYCLES MIN.
- 6.MATING/UNMATING FORCE: 30N/3.06KGf MAX.
- 7.RETENTION STRENGTH:50N OR 30N MIN.FOR 60S±5S

**ELECTRICAL SPECIFICATIONS@25°C UNLESS OTHERWISE NOTED:**

**SPECIFICATION NOTES:**


**ELECTRICAL:**

- 1.VOLTAGE RATING: 125 VAC RMS
- 2.CURRENT RATING: 1.5 AMP
- 3.CONTACT RESISTANCE: 20mΩ MAX.
- 4.INSULATION RESISTANCE: 1000MΩ MIN. AT500V DC.
- 5.DIELECTRIC STRENGTH: 1000 V AC OR 1500V DC RMS AT 0.5mA 50 Hz / 60 Hz FOR 1MINUTE

**ENVIRONMENTAL:**

- 1.STORAGE:-40°C TO +85°C RELATIVE HUMIDITY<80%
- 2.GUARANTEE PERIOD:12 MONTHS
- 3.OPERATION: -40°C TO +85°C
- 4.MANUAL SOLDERING PARAMETERS:24H IR TEMPERATURE: 260±5°C 5~10 SECONDS.

單位: mm	DFTO: Ina	DATE: 2019.03.12
長度公差	角度公差	CHKD: Allen
.0±0.30	0°±2°	DATE: 2019.03.12
.00±0.25		APPVL: W.B.Huang
.000±		DATE: 2019.03.12
		脫模角:
		顏色:
		MATERIAL:
		材質
		TREAT:
		處理
		QTY:
		數量
		SCALE:
		比例 2.5:1



THIRD ANGLE PROJECTION

**ELLAX CORPORATION.**

TITLE:

RJ45-CONNECTOR TAB-UP W/O LED W/ SHIELD

DWG NO.	EL2157-2S28S12	SIZE	REV
DRAWING NO:	EL2157-2S28S12_A	A4	A
PART NO:			
零件編號			1 of 1